



Valve Spring Kits for Evolution/TC-88

VALVE SPRING RETAINERS					VALVE LOCKS			
VT No.	Description	Lock Angle	Valve Stem Size	Valve Spring Diameter	VT No.	Description	Lock Angle	Valve Stem Size
11-7401	Chromoly	10°	All	1.437-1.500"	11-6164	Super Locks +.050 without recess for lock cap	10°	3/8"
11-7411	Chromoly	10°	All	1.500-1.550"				
11-7321	Titanium Double Springs	10°	All	1.500-1.550"				

SPRING KITS INCLUDE SPRINGS, LOCKS, RETAINERS AND LOWER SEATS								
VT No.	Application	Description	Outside	Inner Diameter	Pressure @ Checking Ht.	Pressure @ Opening Ht.	Coil Bind Height	Retainer
11-7702	1984-04 Big Twin	Good Street and Performance Spring up to .600" lift	1.460"	.700"	Lbs-160 In-1.850	Lbs-440 In-1.250"	1.200"	Chromoly
11-7703	1984-04 Big Twin	Good Street and Performance Spring up to .600" lift	1.460"	.700"	Lbs-160 In-1.850	Lbs-440 In-1.250"	1.200"	Titanium
11-7752	1984-04 Big Twin	Super Springs. Street and performance up to .675" lift	1.510"	.745"	Lbs-184 In-1.850	Lbs-422 In-1.250"	1.080"	Chromoly
11-7753	1984-04 Big Twin	Super Springs. Street and performance up to .675" lift	1.510"	.745"	Lbs-184 In-1.850	Lbs-422 In-1.280"	1.080"	Titanium
11-7704	1984-04 Big Twin	Performance Spring up to .675" lift	1.540"	.725"	Lbs-195 In-1.900	Lbs-515 In-1.280"	1.175"	Titanium
11-7705	1984-04 Big Twin	Performance Spring up to .709" lift	1.550"	.710"	Lbs-230 In-1.875	Lbs-700 In-1.200"	1.100"	Titanium



Andrews High Lift Valve .550+ Springs fits 1986-04 Big Twin 1340 Evolution and TC-88. Andrews # 294150. No machining required.

VT No 13-9251



Andrews Anodized TC-88 E-Z Install Pushrods are available in chromoly or aluminum. Installation does not require removal of tank or rocker boxes. Fit 1999-up FXST, FLST, FXD and 1999-16 FLT.

VT No.	Type	Item
11-2188	Aluminum	Pushrods
11-2088	Chromoly	Pushrods
13-9251	High Lift Valve	Springs