



# Lift



Mini-Lift use with table lift to raise bike while on table with 3" to 12" range 600lbs.

VT No.	Item
16-0211	Mini Lift
16-1907	Extender
16-0529	Mini Lift

16-0211 in use



Roller Dolly with nylon wheel and has a capacity of 1250 lbs  
VT No. 16-1999



Tie Downs are 1" x 5'6" in length, 1600 lb strength, 2 per set. Tie downs assist in pair of 12" black nylon straps which acts as cinch around part of the cycle first, then hook tie down to the other end of the loop, to prevent scratching.

VT No.	Item	Brand
48-0180	Tie Downs	V-Twin
48-0650	Tie Down Assist	Wright



16-2008



# V-Lift

16"

16-1993

Standard V-Lifts include a jack which features a foot operated pump and release mechanism. Both units include a stay bar to keep lift in full up position when in use. Units are 4 1/2" in their unextended height. Lift top is compatible with 1936-99 Big Twin frames FXST-FLT-FLST-FLH. The FXR, Sportster and Dyna models require adapters as noted.

VT No.	Height	Jack	Jack Replacement.
16-1993	16"	4 ton	16-2007 6 Ton
16-2008	24"	6 ton	16-2006 4 Ton



All C-G lifts are manufactured in the USA using structural steels that exceed the lifting requirements. The lift mechanism keeps the motorcycle in a vertical position relative to the lifting platform during the entire lifting range. For the safe operation of the lifts, the manufacturer recommends the use of tie downs on all models equipped with eyebolts and installation of hairpin cotter as supplied in safety bar when lift is in use.



Handy B.O.B. Motorcycle Extension  
VT No. 16-1984  
Item 13" Front Extension